



Leak Detectors

## Combustible Gas Leak Detector

# Leakator® 10



Bacharach's Leakator® 10 is a rugged handheld combustible gas leak detector unit loaded with advanced features and low-maintenance that contractors and service professionals demand. This easy-to-use instrument detects acetone, acetylene, ammonia, benzene, butane, ethanol, ethylene oxide\*, gasoline, hexane, hydrogen, industrial solvents, methane, naphtha, natural gas, paint thinners and propane.

## Powerful One-Button Operation

Powered for up to 30 hours of continuous operation with five C alkaline batteries, the Leakator® 10 comes with a flexible 20 inch probe for the location of leaks in any large area or hard-to-reach location. Just turn on the instrument, wait about 55 seconds for the automatic self-check, then point and quickly target potentially hazardous conditions with visual and audible indicators. The Leakator® 10 includes an easy-to-use sensitivity thumb-wheel control to aid in pinpointing the smallest leaks. The self-storing probe keeps the Leakator® 10 probe and sensor protected when not in use.

*\*Only Available by ordering P/N 0019-7063*



## Leakator® 10 Features & Benefits:

- 10 bright red LED's and a speaker that provide visual and audible indications to the presence of gas
- Three operation-status LED's that show power on, sensor operation and low battery
- Simple thumb wheel on/off allowing for one-handed operation
- Solid state plug-in sensor with typical five year life
- 20 inch flexible probe for hard to reach areas
- Operational status LED's in English and International systems
- UL 913 Classified

## Leakator® 10 Specifications

<b>Gases:</b>	Acetone, Acetylene, Benzene, Butane, Ethanol, Ethylene Oxide*, Gasoline, Hexane, Hydrogen, Industrial Solvents, Methane, Naphtha, Natural Gas, Paint Thinners and Propane
<b>Warm-Up Time:</b>	Automatic, Self-Check, Approximately 55 Seconds to Operational Condition
<b>Sensitivity: (Methane-based)</b>	20 ppm
<b>Dimensions:</b>	8.5" x 2.25" x 1.75" (21.6 cm x 5.7 cm x 4.4 cm)
<b>Weight:</b>	18 oz (0.51 kg) without Batteries
<b>Body materials:</b>	Durable ABS Housing with Carrying Strap
<b>Sensor:</b>	Semiconductor Type with Five Year Typical Life – Plug-in Replacement, No User Calibration Required
<b>Probe:</b>	Self Storing 20 inch (51 cm) Flexible Probe
<b>Status Indicators:</b>	Visual - 10 Ultra-Bright Red LED's. Audible - Variable Speed Ticking Sound. Earphone Available for Use in Noisy Environments. Power-On Bright Green LED. Fail Bright Yellow LED. Low Battery Bright Yellow LED.
<b>Operating Temperature Range:</b>	23° to 130° F (-5° to 54° C)
<b>Operating Humidity Range:</b>	10% to 90% Relative Humidity, Non-Condensing
<b>Power:</b>	5 C Alkaline Batteries (Not Included), 30 Hour Typical Battery Life
<b>Approvals:</b>	UL 913 Classified, Intrinsically Safe for Class 1, Division 1, Groups A, B, C and D Hazardous Locations; CE Mark
<b>Warranty:</b>	One Year Limited Warranty

## Leakator® 10 Ordering Information

<b>0019-7051</b>	Leakator® 10 with Flexible 20 inch Probe and Sensor, Instruction Manual, Hard Carrying Case (Batteries Not Included)
<b>0019-7063</b>	Leakator® 10 ETO – For Detection of Ethylene Oxide
<b>0019-0398</b>	Leakator® 10 Replacement Sensor and Matching Resistor
<b>0019-0397</b>	Leakator® 10 Replacement Hard Carrying Case
<b>0019-3091</b>	Leakator® 10 Replacement Flexible Probe Assembly
<b>0051-2529</b>	Leakator® 10 Optional Earphone

### Distributed By:



MADE IN THE USA

Leakator® and Bacharach® are registered trademarks of Bacharach, Inc.  
©Product Bulletin 4180 2010, Bacharach, Inc., all rights reserved. All information is subject to verification.  
December 2010 - REV. 1 Printed in U.S.A.



ISO 9001:2008